

REINFORCED PVC-PU SUCTION

Hoses for aeration

CHARACTERISTICS

Hose made of polyurethane and reinforced with non-deformable red PVC spiral. Non-toxic and suitable for food use. High resistance to pressure and to vacuums, as well as to abrasion, hydrocarbons, atmospheric agents and various chemical products. No mechanical fatigue. Curvature radius 6xDi.

APPLICATIONS

Ideal hose for transporting very abrasive materials (debris, steel fixings, pellets, sand, etc).

TEMPERATURES

From -25°C to +85°C.



∅ Interior mm.	∅ Exterior mm.	Bar Pressure	Empty mH ₂ O	Roll mts.	Code
20	27	5	7	25	AF238020
22	29	5	7	25	AF238022
25	31	5	7	25	AF238025
30	38	5	7	25	AF238030
35	41	4,5	7	25	AF238035
40	48	4	7	25	AF238040
45	54	3,5	7	25	AF238045
50	59	3	7	25	AF238050
55	64	3	7	25	AF238055
60	70	3	7	25	AF238060
63	73	3	7	25	AF238063
70	81	2,5	7	25	AF238070
75	86	2,5	7	25	AF238075
80	92	2,5	7	25	AF238080
90	102	2	7	25	AF238090
100	113	2	6	25	AF238100
102	114	2	6	25	AF238102
110	123	2	6	25	AF238110
127	143	1,5	6	25	AF238127
140	157	1	6	25	AF238140
150	168	1	5	25	AF238150
152	170	1	5	25	AF238152

NOTE

Anti-static quality available upon request (Code AF240).