ESPIROASPERSIÓN



CHARACTERISTICS

Non-toxic hose manufactured through extrusion of vinyl compounds, reinforced with a mesh of polyester threads to provide it with a resistance to breakage from stretching in the elongation. The outer cover is yellow PVC and its interior is black PVC. Very light, flexible and manageable, resistant to atmospheric agents and chemical products.

APPLICATIONS

General irrigation and sprinkling, gardening, horticulture and floriculture.

TEMPERATURES

From -10°C to +60°C

ø Interior mm	ø Interior inches	Weight g/m	Work pressure bar	Burst pressure bar	Roll m	Code
12,5	1/2"	125	8	24	50	AH028001215
15	5/8"	135	8	24	20/25/50	AH028001519
19	3/4"	200	8	24	25/36/50	AH028001925
25	1 1/4"	350	7	21	25/50	AH028002532
30	1 1/4"	550	7	21	25/50	AH028003038

CNI/, AN ECNI/, AN CNI/, AN ECNI/, AN

ECNI AN

ECNI', AN

ECNI AN

ECNI. AX

CNI/...AN

ECNI . AN

ECNI/, AN

ECNI', A



ECNI AN

ECNI , AN

ECNI . A

Camino del fus, 59 • 46470 Massanassa (Valencia - Spain)
P. 96 125 30 55 • Fax 96 125 00 45 • info@tecniman.es • www.tecniman.es