

ABRASIVE DRIVE 12 BAR

CHARACTERISTICS

Hose manufactured on a mandrel with a conductive and abrasion-resistant NR rubber interior. The outer cover is made of abrasion and weather resistant NR rubber. It has an interwoven high-tenacity textile braid.

APPLICATIONS

Hose suitable for pumping sand, abrasive shot and gunite, normally used for surface treatment (sandblasting) or for pumping mortar.

TEMPERATURES

From -40°C to +70°C



Abrasion-resistant hoses

ø Interior mm	ø Outside mm	Weight kg/m	Working pressure (bar)	Bursting pressure (bar)	Roll m	Code
13	29	0.42	12	36	61	AP945013029
16	30	0.58	12	36	61	AP945016030
19	33	0.66	12	36	61	AP945019033
25	40	0.86	12	36	61	AP945025040
30	45	0.98	12	36	61	AP945030045
32	48	1.25	12	36	61	AP945032048
38	56	1.55	12	36	61	AP945038056
51	71	2.25	12	36	61	AP945051071
60	80	2.55	12	36	61	AP945060080
65	85	2.76	12	36	61	AP945065085
70	90	3.23	12	36	20	AP945070090
76	96	3.69	12	36	20	AP945076096
80	102	3.90	12	36	20	AP945080102
100	124	5.06	12	36	20	AP945100124
110	130	5.25	12	36	20	AP945110130
125	151	7.00	12	36	20	AP945125151
152	174	8.63	12	36	20	AP945152174