



CHARACTERISTICS

Red hose made of flexible PVC and reinforced with a rigid, non-deformable PVC spiral, with a smooth inner and outer wall to prevent the formation of sediments and facilitate sterilization. Non-toxic and food-grade. European Directive 2002/72/EC and its latest revision 2007/19/EC, for simulants A, B, C and D₁, according to European regulations EC 1935/2004 and EU 10/2011. Resistant to atmospheric agents, alcohols and chemicals in general. Free of Ca/Pb/Ba and phthalates.

APPLICATIONS

Hose ideal for suction and pressure pumping and transfer of wines, musts, vinegars, beers and spirits (up to 50°) and dairy products.

TEMPERATURES

From -10°C to +60°C

ø Interior mm	Thickness wall mm	Weight g/m	Pressure bar job	Pressure bar breakage	radius of curvature mm	Vacuum _{mH₂O}	Roll m	Code
25	3.5	390	8	24	125	8	50	AD202025
30	4.0	480	8	24	150	8	50	AD202030
32	4.0	500	8	24	160	8	50	AD202032
35	4.2	580	8	24	175	8	50	AD202035
38	4.2	670	8	24	190	8	50	AD202038
40	4.3	685	8	24	200	8	50	AD202040
45	4.5	850	8	24	225	8	50	AD202045
50	5.0	1020	8	24	250	8	50	AD202050
51	5.0	1040	8	24	250	8	50	AD202051
55	5.0	1190	7	21	275	8	50	AD202055
60	5.2	1260	7	21	300	8	50	AD202060
65	5.2	1375	7	21	315	8	50	AD202065
70	5.8	1615	6	18	350	8	50	AD202070
75	5.8	1700	6	18	375	8	50	AD202075
80	6.0	1870	5	15	400	8	50	AD202080
90	6.5	2156	5	15	450	8	30	AD202090
100	7.0	2680	4	12	500	7	30	AD202100
102	7.2	2700	4	12	510	7	30	AD202102
110	7.3	3060	4	12	550	7	30	AD202110
120	7.4	3320	4	12	600	6	30	AD202120
125	7.6	3485	4	12	625	6	30	AD202125
152	8.5	5355	3	9	760	6	30	AD202150