

FIRE PROTECTION

CHARACTERISTICS

Protection made of fiberglass and coated with red, fire-retardant silicone.

APPLICATIONS

Ideal protection for covering pipes and cables in the presence of flames or high temperatures. Complies with EN 45545 and DIN 5510-2 standards

TEMPERATURES

+260°C, +1100°C for short periods of time



Hose protectors

ø Interior mm	ø Outside mm	Roll m	Code
6	8.4	20	CH3500006
8	10.6	20	CH3500008
10	13.2	20	CH3500010
12	15.4	20	CH3500012
13	16.8	20	CH3500013
15	19.2	20	CH3500015
20	24.6	20	CH3500020
22	27	20	CH3500022
25	30.2	20	CH3500025
30	35.8	20	CH3500030
32	38	20	CH3500032
35	41.2	20	CH3500035
38	44.6	20	CH3500038
40	46.8	20	CH3500040
45	52	20	CH3500045
50	57.4	20	CH3500050
55	62.8	20	CH3500055
60	68	20	CH3500060
65	73.2	20	CH3500065
70	78.6	20	CH3500070
75	83.8	20	CH3500075
89	99	15	CH3500089
102	114	15	CH3500102
105	117	15	CH3500105
110	122	15	CH3500110
115	127	15	CH3500115
127	139	15	CH3500127

NOTE Open version with velcro available (code CH351).

