TECNIPUR-S



CHARACTERISTICS

Non-toxic and translucent hose made of 100% polyurethane. It consists of two sheets of polyurethane welded together with an interleaved copper-plated steel spiral, coated with white PVC. Antistatic suitable for installations governed by ATEX regulations. Excellent flexibility, excellent resistance to abrasion and aging.

APPLICATIONS

Hose ideal for transporting all kinds of granules, cereals, sawdust, wood chips, salt, sugar, cement, plastic shavings, etc. For food use according to European regulations EC 1935/2004 and EU 10/2011.

TEMPERATURES

From -30ºC to +80ºC

ø Interior mm	Thickness flexible mm	Weight g/m	Radius of curva-ture mm	Vacuum$_{mH2O}$	Roll m	Code
40	1.0	460	80	6.0	30	AF710040
45	1.0	510	90	5.5	30	AF710045
51	1.0	560	100	5.0	30	AF710051
60	1.0	660	120	4.5	30	AF710060
70	1.0	775	140	4.0	30	AF710070
76	1.0	825	150	3.5	30	AF710076
80	1.1	875	160	3.0	30	AF710080
90	1.1	980	180	3.0	30	AF710090
102	1.1	1000	200	2.5	30	AF710102
110	1.1	1100	220	2.5	30	AF710110
120	1.1	1275	240	2.0	30	AF710120
127	1.1	1350	250	2.0	30	AF710127
130	1.1	1380	260	2.0	30	AF710130
140	1.1	1450	280	2.0	30	AF710140
152	1.1	1550	300	2.0	30	AF710152
160	1.1	1625	330	2.0	30	AF710160
180	1.1	1850	360	2.0	30	AF710180
203	1.1	2100	400	1.8	30	AF710203
225	1.1	2300	450	1.8	30	AF710225
254	1.1	2600	500	1.5	30	AF710254
280	1.1	2850	560	1.5	15	AF710280
305	1.1	3100	600	1.5	15	AF710305
356	1.1	3200	700	1.0	15	AF710356
406	1.1	3600	800	0.8	15	AF710406
450	1.1	3750	900	0.8	15	AF710450
500	1.1	5000	1000	0.8	15	AF710500
550	1.1	5300	1100	0.7	15	AF710550
600	1.1	5600	1200	0.7	15	AF710600