

CHARACTERISTICS

Translucent hose made of polyurethane. With a wall thickness of 1.6 mm. It consists of two polyurethane sheets welded together with an interposed steel spiral, coated with white PVC. Excellent resistance to abrasion, aging, atmospheric agents and mineral oils. Non-toxic and food-grade. Suitable for installations governed by ATEX regulations.

APPLICATIONS

Hose ideal for transporting all kinds of granules, sawdust, wood chips, salt, sugar, cement, plastic shavings, etc. Vacuum cleaning in forests, roads, etc. Complies with FDA and BfR food standards.

TEMPERATURES

From -30°C to +80°C



ø Interior mm	Flexible thickness mm	Weight g/m	Radius of curvature mm	Vacuum _{mH₂O}	Roll m	Code
45	1.6	525	180	6	20	AF720045
50	1.6	560	200	6	20	AF720050
60	1.6	645	240	5	20	AF720060
76	1.6	900	305	5	20	AF720075
80	1.6	960	320	5	20	AF720080
90	1.6	1050	360	5	20	AF720090
102	1.6	1300	410	5	15	AF720100
110	1.6	1325	440	5	15	AF720110
120	1.6	1350	480	4	15	AF720120
125	1.6	1450	510	3	15	AF720127
140	1.6	1525	540	3	15	AF720140
152	1.6	1750	610	3	10	AF720150
160	1.6	1800	640	3	10	AF720160
180	1.6	2400	720	2	10	AF720180
200	1.6	2650	800	2	10	AF720200
220	1.6	3125	880	2	10	AF720220
225	1.6	3250	900	2	10	AF720225
250	1.6	3350	1000	2	10	AF720250
300	1.6	3500	1200	2	10	AF720300

