API TANKWAGEN FITTINGS

API (American Petroleum Institute) fittings are manufactured under API RP-1004 standard. They withstand a working pressure of 10 bar and are used in fuel loading and unloading tanker trucks to connect with the lower loading and unloading valve and drop elbow fittings (or composite hose fittings) and are usually part of the lower loading arms at storage terminals (in fuel storage facilities).

MATERIALS	Aluminum

API HELICAL COUPLING FOR STEAM HOSE - NBR GASKET

DN mm	Spike mm	Code
80	76	CG600080
100	76	CG600100
100	100	CG600105

API FEMALE THREADED COUPLING BSPP - NBR GASKET

DN mm	Female thread inches	Code
80	3"	CG601080
100	3"	CG601100
100	4"	CG601105

API COUPLING WITH MALE THREAD AND 15° INCLINATION - NBR GASKET

DN mm	Female thread inches	Code
100	3"	CG602080
100	4"	CG602100

API COUPLING WITH MALE THREAD, 15° TILT, AND WINDOW

DN mm	Female thread inches	Code
100	3"	CG603080
100	4"	CG603100

API COUPLING WITH ADAPTER AND 15° INCLINATION - NBR GASKET

DN mm	Female thread inches	Code
100	3"	CG604080
100	4"	CG604100

API COUPLING WITH ADAPTER, 15° TILT, AND WINDOW - NBR GASKET

DN mm	Female thread inches	Code
100	3"	CG605080
100	4"	CG605100

API REDUCER AND 15° INCLINATION - NBR GASKET

DN mm	DN mm	Code
100	80	CG606080
100	100	CG606100