COMPRESSED AIR FITTINGS

Compressed air fittings are made of steel and are suitable for working at medium pressure in mines and industrial plants with high safety requirements.

MATERIALS	Steel

HOSE FITTINGS

WITH SAFETY RIMB FOR CLAMPS WITH CLAMP

Hose diameter (mm)
10
13
19
25

CODE CE5110

WITH EAR NUT

DN	Hose diameter (mm)
1/2"	13
3/4"	19
1"	25

CODE CE521

BOSS TYPE COUPLING

DN	Hose diameter (mm)
1/2"	14
3/4"	20
1"	26
1 1/4"	32
1 1/2	38
2"	52
3"	76

CODE CE401

FEMALE THREADED FITTING - DIN 3482

Female thread inches
1/4"
3/8"
1/2"
3/4"
1"
1 1/4"

CODE CE513

MALE THREADED FITTING - DIN 3481

Male thread inches
1/4"
3/8"
1/2"
3/4"
1"
1 1/4"

CODE CE5150

PLUG FITTING ACCORDING TO DIN 3484

CODE CE516102

BOARD

CODE
NBR DA507005L
Viton DA507005V

SAFETY CLAMP

Hose diameter (inches)	Exterior MIN-MAX mm
1/2"	22-29
3/4"	28-34
1"	32-40
1 1/4"	39-49
1 1/2	48-60
2"	60-76
3"	95-114
4"	127-140

CODE CE5720

SAFETY CLAMP WITH CLAW

Hose diameter (inches)	Exterior MIN-MAX mm
1/2"	22-29
3/4"	28-32
1"	35-42
2"	60-73
3"	86-102

CODE CE5721

HIGH SECURITY CLAMPS 4 SCREWS

Hose diameter (inches)	Exterior MIN-MAX mm
1 1/2	55-62
2"	63-70
3"	89-100

CODE CE506

MALE-FEMALE FITTING

Male thread inches	Female thread inches
3/4"	3/4"
3/4"	1"
1"	3/4"

CODE CE520

MALE-TO-MALE FITTING

Male thread inches	Male thread inches
1/2"	1/2"
3/4"	3/4"
1"	1"
3/4"	1"
1 1/2	2"
2"	2"
2"	3"
3"	3"

CODE CE519

HOSE-TO-HOSE SPLICE

Hose diameter (mm)
19
25
38
50

CODE CB137